

## Microphone cables



**Applications:** Flexible low capacity microphone cable, with spiral shield, suitable for the realization of audio assembly.

**Characteristics:**  
 Conductors: O.F.C. red copper  
 Cond. Insulation: Compact PE  
 Core colours: Orange, Transparent  
 Waste filler between conductors  
 Shield: Spiral covering 100%  
 O.F.C. red copper  
 Sheath: PVC  
 Sheath colours: Black, Grey  
**C114:** Black, Grey



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C114	2	2 x 0,25 (23 AWG)	8x0,20	1,5	6,0	100	B	4,7



Sheath colours  
**C260:** Red, Yellow, Green, Blue

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C260	2	2 x 0,25 (23 AWG)	8x0,20	1,5	6,0	100	B	4,7

Production on demand



**Applications:** Extra flex balanced microphone audio cable suitable for realization of audio assembly.

**Characteristics:**  
 Conductors: O.F.C. red copper  
 Cond. Insulation: Compact XLPE  
 Core colours: Red, Transparent  
 Textile filler between conductors  
 Drain wire: O.F.C. tinned copper  
 Shield: Spiral covering 100%  
 O.F.C. red copper  
 Sheath: PVC  
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
T30	2	2 x 24 (0,22 mm <sup>2</sup> )	28x0,10	1,1	5,8	100	B	4,5

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	75	160
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70