

Product code: 202191 EAN: 5905378202191

LED line LITE LED bulb E14 4W 4000K 480lm 220-240V FILAMENT C35 CANDLE



Product description

Manufacturer issues a 3-year warranty for this product. FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 3-year warranty for this product.



High user-safety guaranteed.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Lifespan



Lamp type



Beam angle



LED type



Number of on/off cycles



IP protection rating



Voltage range and voltage type



Lamp's diameter




Material (cover)




LED quantity

Name of the parameter	Value
Klasyfikacja GPC	10000552 - Żarówka/ świetlówki/ diody świetlne
Status	Aktywny (w sprzedaży)
Zawartość netto produktu	1
Jednostka gsm	szt
Fitting	E14
Colour of the light	White
Correlated colour temperature	4000 K
Wattage	4 W
Luminous efficacy	120 lm/W
Luminous flux	480 lm
Energy efficiency class 2019/2015	E
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	3
Diameter	35 mm
Dimmable function	No
Survival factor	0.9
Stroboscopic effect metric SVM	0.4
Lifetime L70B50	25000
Weight	12 g
Type of glass	Clear
Material	Glass
Shape	Candle
Flicker Free	YES
Current	0,034
Supply voltage range and voltage type	220-240V
Frequency of the supply voltage	50/60Hz

Name of the parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96
Lamp's type	C35
Lamp's diameter	35
Beam angle	360 °
Material (cover)	glass
LED type	Filament
LED quantity	4
Lifespan	25000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	98 mm
Product weight with packaging (g)	22 g
Master carton weight (kg)	3
EPREL ID	1596603
Date of first placement on the market	2023-11-02
Flicker metric PstLM	1
Displacement factor Df	0.7
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Chromaticity coordinates x i y (EPREL)	0.38 0.377
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	17
Total luminous flux (EPREL)	480
On-mode power Pon (EPREL)	4
Useful luminous flux Φuse (EPREL)	480
Beam angle in degrees (EPREL)	360
Product code	202191

Pre-packaging

Width [mm]	36
Height [mm]	100
Length [mm]	36
Weight [kg]	22

Cumulative packaging

Number of pieces	100
Width [mm]	200
Height [mm]	225
Length [mm]	380
Weight [kg]	3
Volume [m ³]	0,0171