

Product code: 202269 EAN: 5905378202269

LED line LITE LED bulb E27 7W 2700K 840lm 220-240V FILAMENT A60 GLOBE



Product description

Manufacturer issues a 3-year warranty for this product. FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 3-year warranty for this product.



High user-safety guaranteed.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Lifespan

Lamp type

Beam angle

LED type

Number of on/off cycles



IP protection rating



Voltage range and voltage type



Lamp's diameter



Material (cover)



LED quantity

Name of the parameter	Value
Klasyfikacja GPC	10000552 - Żarówki/ świetlówki/ diody świetlne
Status	Aktywny (w sprzedaży)
Zawartość netto produktu	1
Jednostka gsm	szt
Fitting	E27
Colour of the light	White
Correlated colour temperature	2700 K
Wattage	7 W
Luminous efficacy	120 lm/W
Luminous flux	840 lm
Energy efficiency class 2019/2015	E
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	3
Diameter	60 mm
Dimmable function	No
Survival factor	0.9
Stroboscopic effect metric SVM	0.4
Lifetime L70B50	25000
Weight	32 g
Type of glass	Clear
Material	Glass
Shape	Globe
Flicker Free	YES
Current	0,043
Supply voltage range and voltage type	220-240V
Frequency of the supply voltage	50/60Hz


Name of the parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96
Lamp's type	A60
Lamp's diameter	60
Beam angle	360 °
Material (cover)	glass
LED type	Filament
LED quantity	4
Lifespan	25000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Full box quantity	50 pc
Lamp's warm-up time to 60%	1
Height	108 mm
Product weight with packaging (g)	47 g
Master carton weight (kg)	3,5
EPREL ID	1596596
Date of first placement on the market	2023-11-02
Flicker metric PstLM	1
Displacement factor Df	0.7
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Chromaticity coordinates x i y (EPREL)	0.46 0.411
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	5
Total luminous flux (EPREL)	840
On-mode power Pon (EPREL)	7
Useful luminous flux Φuse (EPREL)	840
Beam angle in degrees (EPREL)	360
Product code	202269

Pre-packaging



Width [mm]	61
Height [mm]	110
Length [mm]	61
Weight [kg]	47

Cumulative packaging



Number of pieces	50
Width [mm]	325
Height [mm]	240
Length [mm]	325
Weight [kg]	3,5
Volume [m ³]	0,02535