

Product code: 202320 EAN: 5905378202320

LED line LITE LED bulb E27 7W 2700K 840lm 220-240V FILAMENT A60 GLOBE DIMMABLE



Product description

Manufacturer issues a 3-year warranty for this product. FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 3-year warranty for this product.



High user-safety guaranteed.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Lifespan



Lamp type



Beam angle



LED type



Number of on/off cycles



IP protection rating



Voltage range and voltage type



Lamp's diameter



Material (cover)



LED quantity

| Name of the parameter | Value |
|---------------------------------------|--|
| Klasyfikacja GPC | 10000552 - Żarówki/ świetlówki/ diody świetlne |
| Status | Aktywny (w sprzedaży) |
| Zawartość netto produktu | 1 |
| Jednostka gśl | szt |
| Fitting | E27 |
| Colour of the light | White |
| Correlated colour temperature | 2700 K |
| Wattage | 7 W |
| Luminous efficacy | 120 lm/W |
| Luminous flux | 840 lm |
| Energy efficiency class 2019/2015 | E |
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 20 |
| Warranty (years) | 3 |
| Diameter | 60 mm |
| Dimmable function | Spec |
| Survival factor | 0.9 |
| Stroboscopic effect metric SVM | 0.4 |
| Lifetime L70B50 | 25000 |
| Weight | 32 g |
| Type of glass | Clear |
| Material | Glass |
| Shape | Globe |
| Flicker Free | YES |
| Current | 0,04 |
| Supply voltage range and voltage type | 220-240V |
| Frequency of the supply voltage | 50/60Hz |


| Name of the parameter | Value |
|--|--------------------|
| Colour rendering index Ra | 80 |
| The lumen maintenance factor | 96 |
| Lamp's type | A60 |
| Lamp's diameter | 60 |
| Beam angle | 360 ° |
| Material (cover) | glass |
| LED type | Filament |
| LED quantity | 4 |
| Lifespan | 25000 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Full box quantity | 50 pc |
| Lamp's warm-up time to 60% | 1 |
| Height | 108 mm |
| Product weight with packaging (g) | 47 g |
| Master carton weight (kg) | 3,5 |
| EPREL ID | 1596590 |
| Date of first placement on the market | 2023-11-02 |
| Flicker metric PstLM | 1 |
| Displacement factor Df | 0.7 |
| Angle for useful luminous flux (EPREL) | Sphere 360 degrees |
| Is the product equipped with an integrated light source? (EPREL) | No |
| Non-directional or directional light source (EPREL) | NDLS |
| Is this product a light source? (EPREL) | Yes |
| Mains or non- mains light source (EPREL) | MLS |
| Chromaticity coordinates x i y (EPREL) | 0.46 0.411 |
| Connected light source (EPREL) | No |
| Colour-tuneable light source (EPREL) | No |
| R9 colour rendering index value (EPREL) | 6 |
| Total luminous flux (EPREL) | 840 |
| On-mode power Pon (EPREL) | 7 |
| Useful luminous flux Φuse (EPREL) | 840 |
| Beam angle in degrees (EPREL) | 360 |
| Product code | 202320 |

Pre-packaging



| | |
|-------------|------------|
| Width [mm] | 61 |
| Height [mm] | 110 |
| Length [mm] | 61 |
| Weight [kg] | 47 |

Cumulative packaging



| | |
|--------------------------|----------------|
| Number of pieces | 50 |
| Width [mm] | 325 |
| Height [mm] | 240 |
| Length [mm] | 325 |
| Weight [kg] | 3,5 |
| Volume [m ³] | 0,02535 |