

Kod: 211605    EAN: 5905378211605

LED line LITE LINIX 120cm 36W 4000K  
4320lm IP65



LED line LITE LINIX are modern LED luminaires with high energy efficiency and durability.

With a light output of 120 lm/W and a wide beam angle of 120°, they provide uniform and comfortable lighting. They are characterized by a high IP65 tightness class and impact resistance (IK07), which makes them an ideal solution for demanding spaces, such as industrial halls, warehouses and garages.

The available models include 120 cm (36 W, 4320 lm) and 150 cm (45 W, 5400 lm) variants, emitting light with a neutral color of 4000 K. Their durability reaches 20,000 hours, and a power factor of 0.95 guarantees stable operation and energy savings.

The luminaires can be connected into continuous light lines, which allows for flexible adjustment of the lighting to large spaces. Thanks to simple assembly and a solid construction, LED line LITE LINIX is an excellent choice for demanding users.



Beam angle



Ambient temperature suitable for operation




Voltage range and voltage type




IK protection rating

Parametr	Wartość
Luminous efficacy	120 lm/W
Power	36 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	4320 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Survival factor	0,9
Mounting type	mixed
Supply voltage range and voltage type	220-240V
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
CRI colour rendering index	80
The lumen maintenance factor	96 %
Beam angle	120 °
Material (cover)	polystyrene
Material (housing)	Polycarbonate
Lifespan	20000
Power Factor	0,95

Parametr	Wartość
Ambient temperature suitable for operation	-20÷40 °C
IEC protection class	II
Full box quantity	30 pc
Lamp's warm-up time to 60%	1
Length	1237 mm
Width	53 mm
Height	27 mm
Product weight with packaging	0,328 g
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	Yes
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	No
Mains or non- mains light source (EPREL)	NMLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
Total luminous flux (EPREL)	4 590
On-mode power Pon (EPREL)	34
Useful luminous flux Φuse (EPREL)	4 590
Beam angle in degrees (EPREL)	120




Opakowanie jednostkowe




Width	51
Height	25
Length	1275
Weight	0,301

Opakowanie zbiorcze



Width	275
Height	190
Length	1280
Weight	9,9

Europaleta



Bulk cartons	480
Weight of a euro pallet	160