


Kod: 211612    EAN: 5905378211612

**LED line LITE LINIX 150cm 45W 4000K  
5400lm IP65**



LED line LITE LINIX are modern LED luminaires with high energy efficiency and durability.

With a light output of 120 lm/W and a wide beam angle of 120°, they provide uniform and comfortable lighting. They are characterized by a high IP65 tightness class and impact resistance (IK07), which makes them an ideal solution for demanding spaces, such as industrial halls, warehouses and garages.


The available models include 120 cm (36 W, 4320 lm) and 150 cm (45 W, 5400 lm) variants, emitting light with a neutral color of 4000 K. Their durability reaches 20,000 hours, and a power factor of 0.95 guarantees stable operation and energy savings.

The luminaires can be connected into continuous light lines, which allows for flexible adjustment of the lighting to large spaces. Thanks to simple assembly and a solid construction, LED line LITE LINIX is an excellent choice for demanding users.




Parametr	Wartość
Luminous efficacy	120 lm/W
Power	45 W
Luminous flux	5400 lm
Correlated colour temperature	4000 K
Standby power	0
Survival factor	0,9
Lifetime L70B50	20 000
Supply voltage range and voltage type	220-240V
Colour	White

Parametr	Wartość
Beam angle	120 °
Ambient temperature suitable for operation	-20/+40 °C
Full box quantity	30 pc
Length	1574 mm
Width	53 mm
Height	27 mm
Product weight with packaging	536 g
Useful luminous flux Φuse (EPREL)	5 400
Beam angle in degrees (EPREL)	120




Opakowanie jednostkowe




Width	51
Height	25
Length	1575
Weight	0,363

Opakowanie zbiorcze



Width	275
Height	190
Length	1580
Weight	11,9

Europaleta



Bulk cartons	480
Weight of a euro pallet	190,5