



Product Code: 248948 EAN: 5901583248948

## LED line® GU10 SMD 220-240V 5,5W 345lm 3000->2200K

### Description

DIM TO WARM is an innovative light source designed to smoothly adjust the color temperature in the range of 2200-3000K. The lamp creates a natural impression of dimmed incandescent light, providing high efficiency through the use of LEDs. By adjusting the light intensity and colour temperature, the user can create a unique indoor atmosphere. Product equipped with optics focusing the beam angle of the light. The product's optics allow the beam of light to be directed to the location of user's choice. Manufacturer issues a 3-year warranty for this product. High user-safety guaranteed. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



DIM TO WARM is an innovative light source designed to smoothly adjust the color temperature in the range of 2200-3000K. The lamp creates a natural impression of dimmed incandescent light, providing high efficiency through the use of LEDs. By adjusting the light intensity and colour temperature, the user can create a unique indoor atmosphere.



High user-safety guaranteed.



Voltage range and voltage type



Material (housing)



Lifespan



Number of on/off cycles



Compatible dimmer type



Product equipped with optics focusing the beam angle of the light. The product's optics allow the beam of light to be directed to the location of user's choice.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 3-year warranty for this product.



Beam angle



LED type



Power Factor



Lamp's diameter

Parameter	Value
Colour temperature	2200-3000K
Colour of the light	white
Luminous efficacy	63lm/W
Ra colour rendering index	90
Energy class	A+
Lamp's warm-up time to 60%	1
Lumen maintenance factor (LLMF)	>0,7
Product weight with packaging (g)	>0,7
Full box quantity	100
Master carton weight (kg)	7,9
Supply voltage range and voltage type	220-240 AC
GU10 fitting	TAK
Beam angle	60°
Material (housing)	Glass

Parameter	Value
LED type	SMD2835
Not dimmable	TAK
Lifespan	30000
Power Factor	0,7
Number of on/off cycles	50000
Lamp's diameter	50
Height	54 mm
Frequency of the supply voltage	50/60Hz
For indoor use	TAK
Warranty (years)	3
Flicker Free	N
Luminous flux	345lm
Wattage	5,5
Compatible dimmer type	TRIAC