


Product code: 249914 EAN: 5901583249914

LED line® UFO T-Series 220-240V AC 100W 13000LM 4000K 90°



Product description

High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs. FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight. This product has been contrued with the use of high quality LIFUD branded driver. Manufacturer issues a 5-year warranty for this product. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



This product has been contrued with the use of high quality LIFUD branded driver.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs.



Lifespan



Lamp's diameter



Material (cover)



LED type



Power Factor



Ambient temperature suitable for operation



IK protection rating



IP protection rating



Voltage range and voltage type



Beam angle



Material (housing)



LED quantity



Number of on/off cycles




IEC protection class

Name of the parameter	Value
Colour of the light	White
Correlated colour temperature	4000 K
Wattage	100 W
Luminous efficacy	130 lm/W
Luminous flux	13000 lm
Energy efficiency class 2019/2015	D
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Warranty (years)	5
Dimmable function	No
Survival factor	0.9
Stroboscopic effect metric SVM	0.4
Lifetime L70B50	50000
Flicker Free	YES


Name of the parameter	Value
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	black
The lumen maintenance factor	96
Lamp's diameter	200
Beam angle	90 °
Material (cover)	polycarbonate
Material (housing)	aluminum
LED type	SMD3030
LED quantity	144
LED manufacturer	Lumileds
Lifespan	50000
Power Factor	0,95
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40 ÷ 45 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Full box quantity	1 pc
Lamp's warm-up time to 60%	1
Height	250 mm
Product weight with packaging (g)	3100 g
Master carton weight (kg)	31
EPREL ID	632050
Date of first placement on the market	2019-10-01
Flicker metric PstLM	1
Energy class	A+
Displacement factor Df	0.95
Angle for useful luminous flux (EPREL)	Wide cone of 120 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	DLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Chromaticity coordinates x i y (EPREL)	0.38 0.377
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
Peak luminous intensity (EPREL)	6369 cd
R9 colour rendering index value (EPREL)	9
Total luminous flux (EPREL)	13000
On-mode power Pon (EPREL)	100
Useful luminous flux Φuse (EPREL)	12200
Beam angle in degrees (EPREL)	90
Product code	249914

Luminous [cd/klm]




C0 - C180 **C90 - C270**

Pre-packaging




Width [mm]	270
Height [mm]	215
Length [mm]	270
Weight [kg]	3,16

Cumulative packaging



Number of pieces	1
Width [mm]	270
Height [mm]	215
Length [mm]	270
Weight [kg]	3,16
Volume [m ³]	0,015

Europallet



Number of pieces	56
Bulk quantity	56
Weight [kg]	176,96
Weight [kg]	176,96
Pallet height [mm]	1649
Quantity in 1 layer	8
Number of layers	7