

Product Code: 470539 EAN: 5907777470539

## LED line® Floodlight PROJECT 100W 11000lm 4000K



### Description

High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs. This product is equipped with a MEANWELL branded driver which ensures reliable and fault-free operation even during prolonged, continuous running. Manufacturer issues a 5-year warranty for this product. The structural design of this product ensures effective heat dissipation. Moisture drainage system, prevents water condensation inside the luminaire and eliminates dewy appearance the signs of visible condensation. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



The structural design of this product ensures effective heat dissipation.



High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs.



This product is equipped with a MEANWELL branded driver which ensures reliable and fault-free operation even during prolonged, continuous running.



The item achieves luminous efficacy at 110lm/W or more.



Voltage range and voltage type



LED type



Beam angle



Material (cover)



IEC protection class



Lifespan



IP protection rating



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Moisture drainage system, prevents water condensation inside the luminaire and eliminates dewy appearance the signs of visible condensation.



Power Factor



LED quantity



IK protection rating



Material (housing)



Ambient temperature suitable for operation




Number of on/off cycles

Parameter	Value
Wattage	100 W
Luminous flux	11000 lm
Luminous efficacy	110 lm/W
Colour temperature	4000 K
Supply voltage range and voltage type	100-240V AC
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
LED type	SMD2835
LED quantity	225
LED manufacturer	Lumileds
MacAdam steps	≤6
Beam angle	120 °
IK protection rating	06
Material (cover)	tempered glass
Material (housing)	DIE-CAST aluminium
Aluminium type	ADC12

Parameter	Value
Colour	Black
IEC protection class	I
Lumen maintenance factor (LLMF)	>0,7
Warranty (years)	5
Width	312 mm
Height	393 mm
Thickness	84 mm
Full box quantity	1 pc
Ambient temperature suitable for operation	-20 / +45 °C
Ra colour rendering index	80
Energy class	A+
Lifespan	100000
Number of on/off cycles	50000
For indoor and outdoor use	YES
IP protection rating	65
Driver Brand	Mean Well

**Opakowanie jednostkowe**



Rodzaj

**Shipping**

**carton**

Szerokość [cm]

**34**

Wysokość [cm]

**13**


Długość [cm]

**38**

Waga [kg]

**5,098**

**Opakowanie zbiorcze**



Ilość sztuk

**1**

Szerokość [cm]

**34**

Wysokość [cm]

**13**

Długość [cm]

**38**

Waga [kg]

**5**

Rodzaj op. zb.

**Cardboard**