



Product Code: 470782 EAN: 5907777470782

## LED line<sup>®</sup> High-Bay UFO 200W 150lm/W 4000K 1-10V 90° RAIDER

## Description

Manufacturer issues a 5-year warranty for this product. The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer. The item achieves luminous efficacy at 150lm/W or more. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.





Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.

Manufacturer issues a 5-year warranty for this product.

5-year warranty



Lamp's diameter



Beam angle



Material (housing)



LED quantity



Power Factor



Ambient temperature suitable for operation



IEC protection class



light intensity using an appropriate dimmer.

The power supply system used allows for smooth adjustment of



The item achieves luminous efficacy at 150lm/W or more.



Voltage range and voltage type



Material (cover)



SMD3030

LED type



Lifespan

50000



IK protection rating





IP protection rating

## LED line ® info@ledline.pl www.ledline.pl

page1of2 Generated 06-01-2021 at 08:01 from the Lumanti PIM system - Ledline



100000h Number of on/off cycles



Parameter	Value
Lamp's diameter	
Height	200 mm
Colour of the light	White
Colour temperature	4000 K
Luminous efficacy	150 lm/W
Luminous flux	30000 lm
Current	0,915
Supply voltage range and voltage type	100-277V AC
Wattage	200 W
Frequency of the supply voltage	50/60Hz
Ra colour rendering index	70
Energy class	A+
Colour	Black
Lamp's warm-up time to 60%	1
Lumen maintenance factor (LLMF)	>0,7
Full box quantity	1 рс
Product weight with packaging (g)	3732 g

Parameter	Value
Beam angle	90 °
Material (cover)	polycarbonate
Material (housing)	Aluminium
LED type	SMD3030
LED quantity	280
Lifespan	100000
Power Factor	0,95
Number of on/off cycles	50000
Ambient temperature suitable for operation	-40 / +45 °C
Warranty (years)	5
IK protection rating	08
IEC protection class	I
IP protection rating	65
LED manufacturer	CREE