



Product Code: 470966 EAN: 5907777470966

## LED line<sup>®</sup> High-Bay UF0 150W 130lm/W 4000K 120° RAIDER 130

## Description

High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs. Manufacturer issues a 5-year warranty for this product. The item achieves luminous efficacy at 130lm/W or more. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.





5-year

warranty

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.

Manufacturer issues a 5-year warranty for this product.



Lamp's diameter



Beam angle



Material (housing)



LED quantity



Lifespan



Number of on/off cycles



IEC protection class

SMD3030
IK 08

LED o

LUMILEDS

130lm

W

voltage 100-277V A (

polycarbonate

COVER



MAX -40 / +45 Ambient temperature suitable for operation





Generated 03-09-2020 at 11:09 from the Lumanti PIM system - Ledline page1of2

Voltage range and voltage type

LUMILEDS branded LEDs.

High luminous efficacy is ensured by the use of high quality

The item achieves luminous efficacy at 130lm/W or more.





LED type

IK protection rating



Power Factor

IP 65

IP protection rating



Parameter	Value
Lamp's diameter	
LED manufacturer	Lumileds
Height	191 mm
Energy class	A+
Colour of the light	White
Colour temperature	4000 K
Luminous efficacy	130 lm/W
Luminous flux	19500 lm
Current	0,686
Supply voltage range and voltage type	100-277V AC
Wattage	150 W
Frequency of the supply voltage	50/60Hz
Ra colour rendering index	80
Warranty (years)	5
Colour	Black
Lumen maintenance factor (LLMF)	>0,7
Beam angle	120 °

Parameter	Value
Material (cover)	polycarbonate
Material (housing)	Aluminium
LED type	SMD3030
LED quantity	200
IK protection rating	08
Lifespan	100000
Power Factor	0,95
Number of on/off cycles	50000
Ambient temperature suitable for operation	-40 ∕ +45 °C
IEC protection class	I
IP protection rating	65
Lamp's warm-up time to 60%	1
Product weight with packaging (g)	3296 g
Full box quantity	1 рс