

Product code: 475473 EAN: 5907777475473

LED line® Elida 40W 4000K 120lm/W 100-277V AC

Product description

LED line® Elida is a fixture for the illumination of both, passageways and other public areas. Appreciated especially by fans of classic design and simplicity. Energy efficiency class E makes LED line® Elida extremely efficient. The product is made of die cast aluminium housing, which ensures high impact strength and resistance to environmental factors, like rain, sunlight or snow. The LED technology makes the ELIDA fixture an energy efficient and functional solution, ensuring low operating costs and long, failure-free service life. The fixture's shape fits perfectly into the surroundings. The manufacturer issues a 5-year warranty for this product.



Power Factor



Mains frequency



Material (cover)



LED type



IK protection rating



Ambient temperature suitable for operation



IP protection rating



Voltage range and voltage type



Beam angle



Material (housing)



LED quantity



Lifespan




IEC protection class


Name of the parameter	Value
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
EPREL ID	1115464
Date of first placement on the market	2022-07-15
Colour consistency in McAdam ellipses	≤5
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Displacement factor Df	0.95
Power Factor	0.95
Colour of the light	White
Luminous efficacy	120 lm/W
Flicker Free	NO
Luminous flux	4800 lm
Current	0.183
Supply voltage range and voltage type	100-277V
Wattage	40 W
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Warranty (years)	5
Beam angle	120 °
Material (cover)	tempered glass
Material (housing)	Aluminium
LED type	SMD2835
LED quantity	64
IK protection rating	08
Lifespan	50000
Ambient temperature suitable for operation	-40--50 °C
IEC protection class	I
Beam angle in degrees (EPREL)	120
Lifetime L70B50	50000
Colour rendering index Ra	80
IP protection rating	65
Lamp's warm-up time to 60%	1
Product weight with packaging (g)	3300 g
Mains or non- mains light source (EPREL)	MLS
Chromaticity coordinates x i y (EPREL)	0.379 0.381
Energy efficiency class 2019/2015	E
Colour consistency in McAdam ellipses	≤5
Connected light source (EPREL)	No
Colour-tunable light source (EPREL)	No
Peak luminous intensity (EPREL)	1850 cd
R9 colour rendering index value (EPREL)	-4
Flicker metric PstLM	1
Dimmable function	No
Survival factor	0.9
Total luminous flux (EPREL)	4800
On-mode power P _{on} (EPREL)	40
The lumen maintenance factor	96
Correlated colour temperature	4000 K
Useful luminous flux Φ _{use} (EPREL)	4800
Stroboscopic effect metric SVM	0.4

Name of the parameter	Value
Product code	475473

Luminous [cd/klm]




Pre-packaging




Type	Shipping carton
Width [mm]	320
Height [mm]	70
Length [mm]	490
Weight [kg]	3,3

Cumulative packaging



Number of pieces	4
Width [mm]	385
Height [mm]	385
Length [mm]	515
Weight [kg]	14
Type of carton box	Box

Europallet



Number of pieces	60
Bulk quantity	15
Weight [kg]	267
Weight [kg]	267
Pallet height [mm]	1725
Quantity in 1 layer	5
Number of layers	3