


Product code: 475558 EAN: 5907777475558

## LED line LITE Outdoor wall mounted luminaire LED 2x3W 4000K IP54 white CILINDER



### Product description



We present the futuristic CILINDER outdoor wall lamp.

- The CILINDER outdoor wall lamp was created for all those who appreciate timeless yet modern solutions.
- The main advantage of the luminaire is that it can be adjusted upwards and downwards.
- Provides complete flexibility to set the upper flux from several to 120 degrees and the lower flux independently. You can adjust the light flux to your needs and preferences.
- CILINDER luminaires are offered in three colours (white, black and grey) and each of them in two colour temperatures 3000K (warm) and 4000K (neutral).
- The solution is energy efficient.

This state-of-the-art product will prove its worth in private buildings, as well as in the walkways and communal areas of elegant residential complexes.



Manufacturer issues a 3-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



IP protection rating



Voltage range and voltage type



Material (cover)



LED type



Power Factor



Ambient temperature suitable for operation



This product is suitable for surface-mounted installation.



Lifespan



Beam angle



Material (housing)



LED quantity



Number of on/off cycles



IK protection rating

| Name of the parameter                 | Value             |
|---------------------------------------|-------------------|
| Correlated colour temperature         | 4000 K            |
| Energy efficiency class 2019/2015     | G                 |
| Colour consistency in McAdam ellipses | ≤6                |
| IP protection rating                  | 54                |
| Warranty (years)                      | 3                 |
| Beam Angle adjustable                 | Yes               |
| Contain icon                          | NonRepl1+NonRepl2 |
| Dimmable function                     | No                |
| Survival factor                       | 0.9               |
| Lifetime L70B50                       | 30000             |
| Number of sources                     | 2 pcs             |
| Coating UV resistance                 | YES               |
| Dimensions (L x W x H.)               | 13,5x11,5x10cm    |
| Current                               | 0,052             |
| Supply voltage range and voltage type | 100- 260V AC      |
| Frequency of the supply voltage       | 50/60Hz           |
| Colour rendering index Ra             | 80                |
| The lumen maintenance factor          | 96                |
| Beam angle                            | 0-120 °           |
| Material (cover)                      | glass             |
| Material (housing)                    | PVC               |
| LED type                              | 2835 SMD          |
| LED quantity                          | 14                |
| Lifespan                              | 30000             |
| Power Factor                          | 0,5               |

| Name of the parameter  | Value              |
|--|--------------------|
| Number of on/off cycles  | 20000              |
| Colour consistency in McAdam ellipses                            | ≤6                 |
| Ambient temperature suitable for operation                       | -20 ÷ 40 °C        |
| For indoor and outdoor use                                       | YES                |
| IK protection rating   | 05                 |
| EPREL ID   | 1366461            |
| Date of first placement on the market                            | 2023-02-13         |
| Displacement factor Df   | 0.7                |
| Form of the product (EPREL)                                      | Source Out         |
| Angle for useful luminous flux (EPREL)                           | Sphere 360 degrees |
| Is the product equipped with an integrated light source? (EPREL) | Yes                |
| Non-directional or directional light source (EPREL)              | NDLS               |
| Is this product a light source? (EPREL)                          | No                 |
| Mains or non- mains light source (EPREL)                         | MLS                |
| Chromaticity coordinates x i y (EPREL)                           | 0.38 0.377         |
| Connected light source (EPREL)                                   | No                 |
| Colour-tuneable light source (EPREL)                             | No                 |
| Total luminous flux (EPREL)                                      | 490                |
| On-mode power Pon (EPREL)  | 6                  |
| Useful luminous flux Φuse (EPREL)                                | 490                |
| Beam angle in degrees (EPREL)                                    | 120                |

## Pre-packaging




Type

Width [mm]  
Height [mm]  
Length [mm]  
Weight [kg]

### Shipping carton

**110**  
**110**  
**110**  
**0,3**


## Cumulative packaging



Number of pieces  
Width [mm]  
Height [mm]  
Length [mm]  
Weight [kg]  
Volume [m<sup>3</sup>]  
Type of carton box

**40**  
**570**  
**460**  
**240**  
**13,1**  
**0,0629**  
**Cardboard**

## Europallet



Number of pieces  
Bulk quantity  
Weight [kg]  
Weight [kg]  
Pallet height [mm]  
Quantity in 1 layer  
Number of layers

**840**  
**18**  
**225**  
**225**  
**1800**  
**6**  
**3**