

# Presslok™ Splice Connectors UB2A, Box

CORNING

## Part Number: UB2A-BOX

With the Presslok™ series of tools and connectors, service providers can meet the demand for enhanced customer services such as high-speed internet, video-on-demand, and video conferencing. Presslok connectors also offer full wire-range capability, increased port size to accommodate up to 2.08 mm (0.082 in) insulation sizes, and solvent resistant plastic construction. As new technologies migrate into the local loop, the importance of reliable connections in the embedded plant has increased exponentially. Each connection is a potential point of failure in high-bandwidth applications, which could require additional time and expense for a technician to repair. That is where the full line of Presslok connectors can really make a difference.

## Features and Benefits

Fast installation

---

Ease of Use

---

Wide Range of Common Wire Guages

---

Factory-installed sealant

---

Dry versions available for Central Offices and Vaults



# Presslok™ Splice Connectors UB2A, Box



## Specifications

### Design

Composition	Gel-filled
No. of connections	Two (2)
Connector type	Tap
Conductor	AWG 26 - 19
Conductor Range	0.4 mm to 0.9 mm

### General Specifications

Product type	Copper Splice Connector
--------------	-------------------------

### Ordering Information

Product Number	UB2A-BOX
EAN Code	4059496710838
Packaging method	Box
Units per delivery	1000/1



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.