



Main

Range of product	Prima
Product or component type	Switch
Device presentation	Complete product
Switch function	1-pole 2-circuit
Cover plate colour tint	White
Connections - terminals	Lift terminals

Complementary

Wiring device mounting	Surface
Rated current	10 AX 250 V AC
Number of cables	2 2.5 mm ²
Cable stiffness	Flexible Rigid
Wire stripping length	11 mm
Material	PA6 FR850
Surface finish	Glossy
Height	61 mm
Width	61 mm
Depth	35 mm
Product weight	0.061 kg

Environment

product certifications	CE
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.