



Main

| | |
|---------------------------|--------------------------------------|
| Range of product | Prima |
| Product or component type | Single socket-outlet side earth |
| Device presentation | Complete product |
| Cover plate colour tint | White |
| Connections - terminals | Lift terminals and screw terminal PE |

Complementary

| | |
|------------------------|-----------------------|
| Wiring device mounting | Surface |
| Rated current | 16 A 250 V AC |
| Number of cables | 2 2.5 mm ² |
| Cable stiffness | Flexible Rigid |
| Wire stripping length | 11 mm |
| Material | PA6 FR850 |
| Surface finish | Glossy |
| Height | 61 mm |
| Width | 61 mm |
| Depth | 43.5 mm |
| Product weight | 0.0655 kg |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0852 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.