



- it turns on/off the light in a BICOLOR type LED strip;
- it changes colors of the light from warm white to neutral
- and cool white in the BICOLOR type light sources;
- possibility of fluent- or step-change of colour temperature;
- change the illumination intensity of the switch's diode;
- dedicated for profiles with max 3-mm thick diffuser mounted
- at the max height of 10 mm;
- for illuminations of 12V/24V voltage;
- max power of 60W/120W;

CORNER LINE, INLINE, INLINE Z, LINE, LINE XL, DEOLINE (P, W and Z),



**Design**Light



**RAILING with circular bar, FLOOR LINE, SKYLINE** 

\*switch is dedicated for LED profiles:


Index: WYL-BICO-01 BICO touch switch for Bicolor strips, 12-24V DC, max 5A EAN code: 5908293402851

Index: WYL-BICO-02W

BICO touch switch for Bicolor strips, 12-24V DC, max 5A with 2-metre 2x0,50 mm2 cable EAN code: 5908293403032

## **Technical drawing:**





41.8 mm

## **Technical data:**









Index: R-2835-600-20-BIK-02 PREMIUM BICOLOR LED strip type 2835, IP20, 120 LED/m, 8-mm width, 6 pts/5 cm, 5-metre roll, power of 10W/m, 1100 lm/m EAN code: 5900652141531

e-mail: mmazek@designlight.pl