PAGE 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PLASTIC SPRAY PRF 202 **Approval date**: 13.10.2006

Supplier: Taerosol Oy

Aakkulantie 21, 36220 Kangasala, Finland

Tel. +358 33 56 56 00 Fax. +358 33 56 56 56

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients considered hazardous to health:

CAS-number	Chemical name	Concentration	<u>Symbol /</u> <u>Risk phrases</u>
64742-49-0	Hydrocarbon solvents	30-40 %	F,Xn,N,R:11-38-65-67,51/53
1330-20-7	Xylen	10-15 %	Xn,R:10-38, 20/21
141-78-6	Ethylacetat	10-20 %	F,Xi,R:11-36-66-67
74-98-6	Propane	10-20 %	F+, R 12
106-97-8	Butane	10-20 %	F+, R 12

3. HAZARDS IDENTIFICATION

Health: Very big concentrations in the air may affect headache daze and indisposition. **Environment:** Toxic to aquatic organisms. May cause long-term adverse effects in the

aquatic environment

Fire: Extremely flammable. Vaporizes easily

Other hazards: The classification R 65 (Harmful: May cause lung damage if swallowed) does

not apply for products in aerosol containers. (EU Directive 67/548 Annex VI 9.4)

4. FIRST AID MEASURES

Eye contact: Flush thoroughly with water at least 10 min. If irritation continues, call a doctor.

Skin contact: Wash contact areas with soap and water. If irritation continues, call a doctor. Polluted clothes may be flammable, they must be moisten before taking off. Clothes must be washed before used again.

Inhalation: If unusual tiredness and queasiness occurs when breathing big concentrations, go to fresh air. If continuing call a doctor.

PAGE 2

Ingestion: When taken internally, rinse with water. DO NOT VOMIT, contact doctor. Ingestion may cause pneumonia.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide, foam, powder and sand for small fires.

Special fire fighting procedures: Risk of explosion if the cans overheat in fire and the pressure rises.

Special protective equipment: Normal protective equipment.

Other recommendations: Do not extinguish with strong water-jet.

6. ACCIDENTAL RELEASE MEASURES

Notification procedures: Dispose material according to current applicable laws and regulations.

Procedures if material is released or spilled: -

Environmental precautions: Prevent spills from entering to groundwater.

Personal precautions: Evacuate all unnecessary people.

7. HANDLING AND STORAGE

Handling: Breathing the vapours and continuous or long-term contacts to skin must be avoided. Keep away from sources of ignition. No smoking. Keep away from children.

Storage: In storage appropriate for extremely flammable aerosols.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Adequate ventilation is recommended.

Respiratory protection: -

Eve protection: Normal industrial eye protection practices should be employed.

Skin protection: All contacts to skin must be avoided. If necessary use PVC-gloves.

PAGE 3

Exposure limits:

Hydrocarbon solvents (arom. < 0, 1 %)

900 mg/m³ (8 h) 1200 mg/m³ (15 min)

Ethylacetat

300 ppm (8 h) 500 ppm (15 min) 1100 mg/m³ (8h) 1800 mg/m³ (15 min)

Xylen

440 mg/m³ (8 h) 660 mg/m³ (15 min)

Propane

800 ppm (8 h) 1100 ppm (15 min) 1500 mg/m³ (8h) 2000 mg/m³ (15 min)

Butane

800 ppm (8 h) 1000 ppm (15 min) 1900 mg/m³ (8 h) 2350 mg/m³ (15 min)

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odour: Clear, colourless liquid

Boiling point: -20 °C (Prop./But.)

Melting point: -

Flash point: $< 0^{\circ}$ C

Auto flammability: -

Density: 740 kg/m^3

Explosion limits: 2,3-9,5 vol %

Viscosity at 40 °C:

Solubility in water: Insoluble

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL DATA

Inhalation: Very big concentrations in the air may effect headache daze and indisposition.

Harmful by inhalation and in contact with skin

Eye irritation: Irritating to eyes.

Skin irritation: Irritating to skin. Repeated exposure may cause skin dryness or cracking

Other acute toxicity: Harmful: May cause lung damage if swallowed

PAGE 4

12. ECOLOGICAL INFORMATION

Environmental fate and effects: Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment

Additional: Insoluble in water. Evaporates partly from water or soil. Big quantities may pollute soil and ground water.

13. DISPOSAL CONSIDERATIONS

Waste disposal: Empty cans must be disposed according to laws and environment officials. **RCRA Information:**-

14. TRANSPORT INFORMATION

UN-Number: 1950

ICAO/IATA: 2.1

RID/ADR: 2, (ADR)

IMDG: 2.1

EmS No F-D, S-U

15. REGULATORY INFORMATION

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding +50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition. No smoking. Keep away from children.

Warning symbol(s)

F+ Extremely flammable

Xn Harmful

N Dangerous for the environment

SAFETY DATA SHEET PAGE 5

Risk phrase(s)

R 12	Extremely flammable	
R 20/21	Harmful by inhalation and in contact with skin	
R 36/38	Irritating to eyes and skin	
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in	the
	aquatic environment	
R 66	Repeated exposure may cause skin dryness or cracking	

Safety phrase(s)

S 2	Keep out of the reach of children.	
S 16	Keep away from sources of ignition – No smoking	
S 23	Do not breathe vapour.	
S 24	Avoid contact with skin and eyes.	

16. OTHER INFORMATION

List of Risk phrases regarding the chemicals

R 10	Flammable
R 11	Highly flammable
R 12	Extremely flammable
R 20/21	Harmful by inhalation and in contact with skin
R 36	Irritating to eyes
R 38	Irritating to skin
R 43	May cause sensitization by skin contact
R 60	May impair fertility
R 61	May cause harm to the unborn child
R 62	Possible risk of impaired fertility
R 63	Possible risk of harm to the unborn child
R 65	Harmful: May cause lung damage if swallowed
R 66	Repeated exposure may cause skin dryness or cracking
R 67	Vapours may cause drowsiness and dizziness.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Further information

Source of information

The information contained herewith is based on the information from raw material deliverers