

**1. PRODUCT AND COMPANY IDENTIFICATION****Product name:** PRF BAJOL**Approval date:** 23.1.2006**Supplier:** Taerosol Oy

Aakkulantie 21, 36220 Kangasala, Finland

Tel. +358 33 56 56 00

Fax. +358 33 56 56 56

**2. COMPOSITION / INFORMATION ON INGREDIENTS****Ingredients considered hazardous to health:**

<u>CAS-number</u>	<u>Chemical name</u>	<u>Concentration</u>	<u>Symbol / Risk phrases</u>
64742-49-0	Hydrocarbon solvents	30-50 %	F, Xn, N, R:11-38-65-67,51/53
	Synthetic oil	20-40 %	
74-98-6	Propane	10-20 %	F+, R 12
106-97-8	Butane	10-20 %	F+, R 12

**3. HAZARDS IDENTIFICATION****Health:** Very big concentrations in the air may affect headache, daze and indisposition. Harmful by inhalation and in contact with eyes. Repeated exposure may cause skin dryness.**Environment:** Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment**Fire:** Extremely flammable.**Other hazards:** The classification R 65 (Harmful: May cause lung damage if swallowed) does not apply for products in aerosol containers. (EU Directive 67/548 Annex VI 9.4)**4. FIRST AID MEASURES****Eye contact:** Flush thoroughly with water at least 10 min. If irritation continues, call a doctor.**Skin contact:** Wash contact areas with soap and water. If irritation continues, call a doctor. Polluted clothes may be flammable, they must be moisten before taking off. Clothes must be washed before used again.**Inhalation:** If unusual tiredness and queasiness occurs when breathing big concentrations, go to fresh air. If continuing call a doctor.

**Ingestion:** When taken internally, rinse with water. DO NOT VOMIT, contact doctor. Ingestion may cause pneumonia.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide, foam, powder and sand for small fires.

**Special fire fighting procedures:** Risk of explosion if the cans overheat in fire and the pressure rises.

**Special protective equipment:** Normal protective equipment.

**Other recommendations:** -

## 6. ACCIDENTAL RELEASE MEASURES

**Notification procedures:** Dispose material according to current applicable laws and regulations.

**Procedures if material is released or spilled:** -

**Environmental precautions:** Prevent spills from entering to groundwater.

**Personal precautions:** Evacuate all unnecessary people.

## 7. HANDLING AND STORAGE

**Handling:** Breathing the vapours and continuous or long-term contacts to skin must be avoided. Keep away from sources of ignition. No smoking. Keep away from children.

**Storage:** In storage appropriate for extremely flammable aerosols.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Ventilation:** Adequate ventilation is recommended.

**Respiratory protection:** -

**Eye protection:** Normal industrial eye protection practices should be employed.

**Skin protection:** All contacts to skin must be avoided. If necessary use PVC-gloves.

**Exposure limits:**

Hydrocarbon solvents (arom. &lt; 0, 1 %)

500 ppm (8h)	630 ppm (15 min)
1800 mg/m <sup>3</sup> (8 h)	2300 mg/m <sup>3</sup> (15 min)

Propane

800 ppm (8 h)	1100 ppm (15 min)
1500 mg/m <sup>3</sup> (8h)	2000 mg/m <sup>3</sup> (15 min)

Butane

800 ppm (8 h)	1000 ppm (15 min)
1900 mg/m <sup>3</sup> (8 h)	2350 mg/m <sup>3</sup> (15 min)

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance and odour:</b>	Clear, yellowish liquid
<b>Boiling point:</b>	50 °C (Hydrocarbon solvents), -20 °C (Prop./But.)
<b>Melting point:</b>	-
<b>Flash point:</b>	< 0°C
<b>Auto flammability:</b>	-
<b>Density:</b>	660 kg/m <sup>3</sup>
<b>Explosion limits:</b>	2,3 – 9,5 vol % (Propane)
<b>Vapour pressure:</b>	-
<b>Viscosity at 40 °C:</b>	-
<b>Solubility in water:</b>	Insoluble

**10. STABILITY AND REACTIVITY**

---

**11. TOXICOLOGICAL DATA****Inhalation:** Very big concentrations in the air may affect headache, daze and indisposition.**Eye irritation:** -**Skin irritation:** Irritates slightly skin. Repeated exposure may be irritating to skin.**Other acute toxicity:** Harmful: May cause lung damage if swallowed

**12. ECOLOGICAL INFORMATION**

**Environmental fate and effects:** Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment

**Additional:** Insoluble in water. Evaporates partly from water or soil. Big quantities may pollute soil and ground water.

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal:** Empty cans must be disposed according to laws and environment officials.

**RCRA Information:-**

**14. TRANSPORT INFORMATION**

**UN-Number:** 1950

**ICAO/IATA:** 2.1

**RID/ADR:** 2, (ADR)

**IMDG:** 2.1

**EmS No** F-D, S-U

**15. REGULATORY INFORMATION**

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding +50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition. No smoking. Keep away from children.

**Warning symbol(s)**

F+

Extremely flammable



Xi

Irritant



N

Dangerous for the environment



**Risk phrase(s)**

R 12	Extremely flammable
R 38	Irritating to skin
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

**Safety phrase(s)**

S 2	Keep out of the reach of children.
S 16	Keep away from sources of ignition – No smoking
S 24/25	Avoid contact with skin and eyes.

## 16. OTHER INFORMATION

**List of Risk phrases regarding the chemicals**

R 11	Highly flammable
R 12	Extremely flammable
R 38	Irritating to skin
R 65	Harmful: May cause lung damage if swallowed
R 67	Vapours may cause drowsiness and dizziness.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

**Further information****Source of information**

The information contained herewith is based on the information from raw material deliverers