

GS2200-15357

PowerRoam 2200W Portable Power Station-EU Version

Features:

Be Ready for Anything:

Be prepared for emergency situations. Keep appliances in your home running with PowerRoam, such as kettle, toaster, coffee maker and fridge.

PowerZip Technology:

Featured with the PowerZip Tech, the PowerRoam GS2200 can be fully recharged in 1.5 hours.

U-Turbo Technology:

U-Turbo technology powers up the solar generator allowing support for high-wattage appliances of up to 3500W.

Premium EV-Rated Battery:

Partnered with world-renowned BYD to provide premium LiFePO4 EV batteries with a lifespan 6 times longer than traditional lithium-ion batteries.

Battery Management System(BMS):

The BMS regulates the batteries inside and manages battery health using AI algorithms, which allows the PowerRoam to run 6000 cycles to 60% capacity, and 3000 cycles to 80% capacity.

Dedicated PowerRoam APP:

Adjust power settings, run diagnostic checks, set maximum power levels, and confirm the remaining charges of your PowerRoam, all in real time from your mobile device.



GS2200-15357

PowerRoam 2200W Portable Power Station-EU Version

Specification:

***Capacity:** 2048Wh 40Ah 51.2V (640000mAh 3.2V)

***EV-Rated LFP Batteries Cycle Life (80%):** 3000 times

***PowerZip Technology:** Recharge to 100% in 1.5 hrs

***U-Turbo Technology:** Compatible with most heavy-duty appliances & power tools

*Support BMS/Entry level UPS/WIFI/Bluetooth/APP Function

***4 lighting modes:** Strong, Standard, Flash, and SOS

***14 Ports output:**

AC: 2300W*4 (Pure Sine Wave; Peak: 3500W)

USB-C1: 140W; USB-C2: 100W

USB-C3/C4: 45W

USB-A: 22.5W*2 (Dual-Port: 15W Max)

Car charger *1 (12V/10A 120W Max)

Anderson Output*1(12V/25A 300W Max)

DC5521*2(Single-Port 12V/5A 60W Max)

Car Charger + Anderson + DC521 X2= 300W Max

***Output Total:** 2500W max

***Input:**

AC: 200-240V,50Hz,10AMax

Solar charging*2: 12-60V, 15A(Single-Port: 600W Max, Dual-Port: 1200W Max-Fully charged in about 2.5 hours)

DC/Car Charger: 12V / 24V=8A Max

***Display:** 4.7 inch LCD

***PC+ABS Shell:** UL 94 V-0 Certified Flame Resistant

***Dimensions:** 59x 25 x 29 (cm)

***Weight:** Around 25.5kg

***Charging Temperature:** 0°C-40°C (32°F-104°F)

***Discharging Temperature:** -10°C-40°C (14°F~104°F)