cell chemistry:Li-loncell size:AAA (10430)cell type:round cell

Conditions

nominal output voltage: 1.5 V when SOC (state of charge) of battery is >10% reduced output voltage: 1.05 V when SOC (state of charge) of battery is <10%

capacity

nominal: 500 mAh discharge at 0.2C minimum: 400 mAh discharge at 0.2C discharge at 0.2C discharge at 0.5C

ta: 20°C; EV(Discharge End Voltage): 0.9V

discharge ta: 0....45°C

max. continuous

discharge current: 500 mA nom. discharge current: 100 mA

charge via type-C connector (with USB charger)

supply voltage: 5 V \pm 0.25V charge current: 100 mA \pm 10% charge time: 2.75 h \pm 0.5h

external charge (at battery + / - poles) is not allowed; charge battery via type-C connector only

internal resistance: n/a at 1kHz, sine wave measurement

according to IEC 896-2

built-in li-ion battery: 3.7 V / 200mAh

energy: 0.74 Wh

output protection functions

overload cut-off current: 1 A \pm 0.3A

deep discharge protection function

cut-off voltage of int. battery: 2.6 V ± 0.3V

LED charge indicator visible on the opposite side of the type-C socket

flashes red during charge

lights green at end of charge (battery fully charged)

life time expectance

(C>70% of min. capacity) ≥ 1200 cycles at 0.2C charge/discharge rate

self discharge: ≤ 2 %/month at 20°C ≤ 5 %/month at 30°C

≤ 10 %/month at 40°C

ambient temperature

range: 0...45 °C charge

- 20...60 °C discharge


- 20...25 °C storage max. 1year - 20...45 °C storage max. 3months

recommended SOC: 30...50 % for long-time storage

(SOC = state of charge)

mechanical specifications

cell dimensions (incl. sleeve)





114		
	ANSMANN Specifications for model:	AAA (10430) Li-lon Battery 1.5V 500mAh w. type-C charge
		1.5V 500111A11 W. type-C charge
	data sheet no. / part no.	1311-0028
	s.n.	705163
	author / date	TG / 26.10.2022