

Guitar flexible cables



Applications:
Flexible cable with inner sheath in conductive PVC, for guitars and musical instruments.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: PPE
 Core colour: White
 Inner sheath: Special conductive PVC
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C300	1	1 x 0,22 (24 AWG)	7x0,20	1,5	6,0	100	B	4,4
C285	1	1 x 0,50 (20 AWG)	7x0,30	1,7	6,2	100	B	4,6

nightly blue®



Carbon screened guitar cable



Applications:
Professional audio cable for musical instruments, with conductive shield and high density dielectric.

Characteristics:
 Conductor: O.F.C. red copper
 Cond. Insulation: PPE
 Core colour: White
 Special screen: Carbon-PVC
 Shield: Spiral covering 100%
 O.F.C. red copper
 Sheath: Flame Retardant PVC
 CEI 20-22/II°
 Sheath colour: Blue-night



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
TSK 1031	1	1 x 0,50 (20 AWG)	16x0,20	4,5	7,3	100	B	6,5

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
45		70
Test Voltage V	Max rated Voltage AC - V	Operative Temperature °C
1000	49	-15 / +70