



Applications:
Flexible braided shielded mini-coaxial cable for R.G.B. video signals.

Characteristics:
 Conductor: stranded in O.F.C. red copper
 Insulation: Compact PE
 Shield: Braided covering 95% O.F.C. silver plated copper PVC
 Sheath: PVC
 Sheath colours: Black, White, Red, Green, Blue



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format.	External Core	External Inner Sheath	External Cable Diameter	Reel or Spool (* pag. II)		
							mm.	mt.	Type
RGB-75	1	1 x 75 Ω (0,08 mm ²)	9x0,10 CW	1,5		2,8	100	B	1,2

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
210				67	
Velocity of propagation %	Impedance	Voltage		Operative Temperature	
%	Ω ± 3%	V		°C	
66	75	1500		-15 / +70	
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
19,2	27,9	40,7	59,2	85,3	101,0



Applications:
Extra flexible coaxial cable for video frequency, suitable for professional BNC connectors (crimp type) and for the realization of cables and extensions for VHF and UHF signals.

Characteristics:
 Conductor: stiff wire in CW
 Insulation: PE
 Shield: Braided covering 80% O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format.	External Core	External Inner Sheath	External Cable Diameter	Reel or Spool (* pag. II)		
							mm.	mt.	Type
RG 59 eXtra	1	1 x 75 Ω (0,26 mm ²)	1x0,58 CW	3,7		6,1	100 250 500	B B B	4,5

Conductor Resistance		Capacity Core/core		Capacity Core/shield	
Ω/Km ± 5%		pF/mt		pF/mt	
158				67	
Velocity of propagation %	Impedance	Voltage		Operative Temperature	
%	Ω ± 3%	V		°C	
66	75	2000		-15 / +70	
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
7,6	11,1	16,2	23,2	34,3	38,7