

## Emmi-20 HC Plus



### technical specifications Emmi-20 HC Plus

#### Description:

Universal device with stainless steel oscillating tank and stainless-steel case.  
Timer 1-60 min., Continuous operation, heating and ultrasonic power regulator.

#### Dimensions:

Tackle outside (L x B x H): 310 x 180 x 240 mm  
Tub Indoor (L x W x H): 240 x 140 x 70 mm  
Basket Indoor (L x W x H): 210 x 120 x 45 mm  
Mesh of the Basket (Ø): 6 mm

#### Content:

When content: 2,6 liters  
Filling volume: 2 liters

#### Equipment:

Internal tank: Stainless steel 1.4301  
Housing: stainless steel 1.4301  
Degree of protection: IP 32  
Drain tap: No  
Timer: 1-60 min / continuous operation  
Heating: 30-80 ° C  
Ultrasonic power regulator: 40 / 60 / 80 / 100%

#### Technical specifications:

Transducers: 2 PZT broad beam transducers System  
HF generator: overload protected, constant power  
Modes: Easy half-wave  
Operating frequency: 40 kHz  
Ultrasonic power: max. 120 Watt  
Heating power: 150 Watts  
Power supply: 50/60 Hz  
Power supply: 220 - 240 V



1. Cover – stainless steel
2. Basket - stainless
3. Tub – stainless steel
4. Power cable
5. Timer
6. ON/OFF
7. 3 stages ultrasound power (Emmi<sup>+</sup>-20HC+, Emmi<sup>+</sup>-30HC+, Emmi<sup>+</sup>-40HC+, Emmi<sup>+</sup>-60HC+)
8. Switch for temperature setting regulator
9. Outlet valve (Emmi<sup>+</sup>-30HC+, Emmi<sup>+</sup>-40HC+, Emmi<sup>+</sup>-60HC+)