

# **Emmi 30 HC Plus**





Ultrasonic power regulator: 40% / 60% / 80% / 100%

## **Technical specifications Emmi 30 HC Plus**

### **Description:**

Universal device 3,0 l with stainless steel oscillating tank and stainless-steel case, timer 1-60 min., continuous operation, heating, and ultrasonic power regulator.

## **Dimensions:**

Tackle outside (L x B x H):  $310 \times 180 \times 260$  mm Tub Indoor (L x W x H):  $240 \times 135 \times 100$  mm Basket Indoor (L x W x H):  $210 \times 120 \times 75$  mm

Mesh of the Basket (Ø): 8 mm

#### **Content:**

When content: 3.0 litters Filling volume: 2.2 litters

#### **Equipment:**

Internal tank: Stainless steel 1.4301 Housing: stainless steel 1.4301 Degree of protection: IP 32

Drain tap: Yes

Timer: 1-60 min / continuous operation

Heating: 30-80 ° C

Ultrasonic power regulator: 40 /60 / 80 / 100%

## **Technical specifications:**

Transducers: 3 PZT broad beam transducers System HF generator: overload protected, constant power.

Modes: Easy half-wave Operating frequency: 40 kHz Ultrasonic power: max. 180 Watt Heating power: 150 Watts

Power supply: 50/60 Hz Power supply: 220 - 240 V

#### EMMI\*-20HC+, EMMI\*-30HC+, EMMI\*-40HC+, EMMI\*-60HC+



- 1. Cover stainless steel
- 2. Basket stainless
- 3. Tub stainless steel
- Power cabl
  Timer
- 6. ON/OFF
- 7. 3 stages ultrasound power
- (Emmi-20HC+, Emmi-30HC+, Emmi-40HC+, Emmi-60HC+) 8. Switch for temperature setting
- Switch for temperature settin regulator
  Outlet valve
  - (Emmi\*30HC+, Emmi\*40HC+, Emmi\*60HC+)